

2500 Litre Site Towable Fuel Bowser



| Height | 1945mm |
|------------------------------|--------|
| Width | 1880mm |
| Length | 3630mm |
| Empty Weight | 1600kg |
| Full Weight | 3612kg |
| Max. hose length | 14m |
| Steel thickness (inner tank) | 3mm |
| Steel thickness (outer tank) | 4mm |

Standard Specification

- » 1" check valve
- » 1/2" pressure relief valve
- » 2" fill point
- » 3" splash fill point
- » 1/2" generator feed and return connections
- » Rotary fuel contents gauge

Standard Fuel Dispensing Pump Package

- » 4 Stroke Petrol Engined Pump with Oil Alert
- » 6M x 1' Dispensing Hose
- » K33 3Digit Flowmeter
- » 11/2 BSP Filter Head
- » High Flow Auto Shut Off Trigger
- » Particle Filter for High Flow

Special Features

- » Fully compliant with current environmental regulations
- » All-steel construction for long term reliable service
- » Steel tank and heavy duty integral chassis make these units the strongest and most durable on the market
- » 110% bunded & fully compliant with current environmental regulations
- » Reinforced, heavy duty galvanised tubular steel chassis
- » Tough site specification with heavy duty running gear
- » Baffled inner tank for incresed stability when in transit

NATIONWIDE SERVICE 24/7 NEXT DAY DELIVERY



Cross Plant Hire Ltd | Prospect House | Ramsbottom | Lancashire BLO OED





